

10L Black UN Bucket For Liquids

PACKAGING DESCRIPTION – RANGE PRIME

Commercial reference	ROPAC® 10 LL
Shape	Cylindrical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	289 mm
Height incl. lid	282 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	0.99 cm ³ /24 ^o for 21% oxygen
Inner pressure resistance	100 kPa during 30 minutes
UN certified for	II and III for liquids 1.6 / III for liquids 2.4
Packaging classification	Dangerous liquid goods Y.16 & Z 2.4
Handling	Plastic handle
Raw material	HDPE
Stackability	Y 195 kg & Z 280 kg (28 days at 40°C)
Option	Flex-spout on request



PAIL CHARACTERISTICS – REFERENCE 7564006

Volume brim full	13,6 l (3.59 US gallons)
Volume under lid	12 l (3.17 US gallons)
UN certified for a maximum weight of content	Y 1.6 g/cm ³ and Z 2.4 g/cm ³
Weight	646,1 g
Internal diameter at top	265 mm
Embossing	UN 1H2 /Y 1.6 - Z 2.4 /100 /-- /F/ BVT260840
Decoration type	Digital print
Decoration area	On request
Standard palletisation (800x1200 NIMP15)	154 pails (11 piles of 14 pails)
Height of pallet	1,80 m



LID CHARACTERISTICS – REFERENCE 7584010

Weight	284 g (without gasket)
Diameter	264,2 mm
Embossing	ROPAC 10-20 HLIQ
Gasket	PUR
Standard palletisation (800x1200 NIMP15)	484 lids (11 piles of 44 lids)
Height of pallet	1,60m



These specifications are without legal warranty and subject to changes without notification.

September 2018/ SV

