

## 12.7L Round White Bucket

SuperLift ø293 mm 12,7 ltr

**Product no:** 8126  
**Shape:** Round  
**Available lids:** 293SL (Standard)  
 4128 (Membrane)  
 4123 (Vented)  
 4116 (Standard with centering ring)  
 4115 (Other)



VOLUME			
<b>Volume under lid:</b>	13 l ± 130 ml	<b>Volume brimful:</b>	13.6 l ± 130 ml
DIMENSIONS			
<b>External diameter top:</b>	295.5 mm ± 3 mm	<b>Height:</b>	258 mm ± 1 mm
<b>External diameter bottom:</b>	249.8 mm ± 1 mm		
WEIGHT			
<b>Weight:</b>	386 g ± 12 g	<b>Weight metal handle:</b>	49 g ± 5 g
<b>Weight plastic handle:</b>	21 g ± 2 g		
PERFORMANCE			
<b>Stackability - dynamic:</b>	Max: 45 kg top load on bottom container at 23°		
<b>Stacking tests:</b>	The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.		
CLOSURE SYSTEM		HANDLE	
<b>Lid type options:</b>	Membrane, Standard, FlakeFree	<b>Standard handle:</b>	Metal with roller grip
<b>Closure type:</b>	Peel-off	<b>Optional handle:</b>	Flexible plastic hanging
<b>Protective collar:</b>	Yes		
<b>Tamper Evidence type:</b>	Tamper Evidence tab		
DECORATION			
<b>Decoration available:</b>	Dry Offset, IML	<b>Decoration area offset:</b>	810 X 180 mm
RAW MATERIAL			
<b>Raw material options:</b>	PP	<b>Hot filling:</b>	85-95° C
<b>Masterbatch colours:</b>	Colours according to RPC Superfos standard selected pantone colours.		
<b>Hot temperatures:</b> The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.			
<b>Cold temperatures:</b> Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			