

15L White UN Bucket For Solids

PACKAGING DESCRIPTION – RANGE SECURE

Commercial reference	ROPAC® MP 15 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADNR, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	320 mm
Height incl. lid	286,5 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	1,38 cm ³ / day for 21% oxygen
UN certified for	Dangerous solid goods
Packaging classification	II and III (group b and c of each class, excepted 1 and 2).
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 216 kg / 24 h /23°C
Option	Flex-spout on request



PAIL CHARACTERISTICS – REFERENCE 7515006

Volume brim full	17,9 l (4.73 US gallons)
Volume under lid	16,4 l (4.33 US gallons)
UN certified for a maximum weight of content	23 kg
Weight with handle	717,25 g
Internal diameter at top	303 mm
Embossing	Ⓜ 1H2/Y23/S/--/F/BVT 26088
Decoration type	Digital print
Decoration area	On request
Standard palletisation (800x1200 NIMP15)	160 pails (8 piles of 20 pails)
Height of pallet	1,78 m



LID CHARACTERISTICS – REFERENCE 7542031

Weight without gasket	220 g
Diameter	300 mm
Embossing	Ⓜ MP 15-20H
Gasket	SEBS
Standard palletisation (800x1200 NIMP15)	480 lids (8 piles of 60 lids)
Height of pallet	1,67 m

