

25L Blue Tight-Head Steel Drum

Packaging type: 1A1 Description:
Drum, steel, non-removable head

Stainless: No Metal thickness Body: 0.50 mm Base: 0.50 mm Head: 0.50 mm Tare: 2.60 kg Capacity: 25 litres
Tinned: No Diameter: 283 mm Height: 484 mm Rolling hoop(s): No Handle: Tinplate strap handle on head

CLOSURES: No in Head: 1 No in Body: 1 Closures may be any of the following:

Steel	Steel
Size: 2"	Size: 3/4"
Type:	Type:
Screwbung	Screwbung
Maker:	Maker:
Tri-Sure	Tri-Sure
Pro-Seal	Pro-Seal
Technocraft	Technocraft
Overcap: <input type="checkbox"/>	Overcap: <input type="checkbox"/>
Washer/wad and Closure Torque	Washer/wad and Closure Torque
Rubber 30 Nm	Rubber 10 Nm
Plastics 40 Nm	Plastics 15 Nm

Special Notes:

Optional: 2 x wire drop handles on body

There may be additional options please see full report(s)

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:		The packaging is approved, as provided in the relevant transport rule, to contain liquids of:		
		packing group	density (d)	gross mass (kg)
DROP HEIGHT (m)	1.4	I	-	-
LEAKPROOFNESS (kPa)	30			
STACKED AT 3m with RD (d)	1.9	II	1.3	36
INTERNAL PRESSURE (kPa)	200	III	1.9	51

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

Packagings of the sample specifications shall bear the marking:

 1A1/Y1.4/200/**/GB/1065

** To be replaced by the last two digits of the year of manufacture

Revalidation due by: 31/12/ 2020

For further details see www.vca.gov.uk

Signed:

Keith F B White

Keith F B White, Principal Consultant VCA DGO

Amendments or additions to this certificate or the design type specification described therein other than those authorised by the certifying body render the certificate invalid