

## 25L Blue UN Approved Jerry Can with Bung

Capacity: 25 litres      Height: 445 mm      Bodymass: 1.35 Kg      Tare: 1.384 kg  
 Section dimensions: 285 length x 285 width      Test Contents: Tested with water and ethylene glycol for liquids  
 Handle: Integral on top  
 CLOSURES: No in Head: 1      No in Body: 0

|  |   |  |   |  |
|--|---|--|---|--|
| Plastics<br>Size: 2"<br>Type:<br>6N Plastics threaded solid bung<br>Maker:<br>Gem<br>Overcap: <input type="checkbox"/><br>Washer/wad and Closure Torque<br>EPDM O-ring 18 Nm<br>Nm | Plastics<br>Size: 2"<br>Type:<br>6N Internally threaded plastics bung<br>Maker:<br>Gem<br>Overcap: <input type="checkbox"/><br>Washer/wad and Closure Torque<br>EPDM O-ring 18 Nm<br>Nm | Plastics<br>Size: 2"<br>Type:<br>6N bung with 3/4" inset bung with vent<br>Maker:<br>Tri-sure<br>Overcap: <input type="checkbox"/><br>Washer/wad and Closure Torque<br>EPDM O-ring 18 Nm<br>Nm | Plastics<br>Size: 2"<br>Type:<br>6N Screwbung<br>Maker:<br>Tri-Sure<br>Overcap: <input type="checkbox"/><br>Washer/wad and Closure Torque<br>EPDM 18 Nm<br>Nm | Plastics<br>Size: 2"<br>Type:<br>6N bung with 3/4" inset bung<br>Maker:<br>Tri-Sure<br>Overcap: <input type="checkbox"/><br>Washer/wad and Closure Torque<br>EPDM O ring 18 Nm<br>Nm |
|--|---|--|---|--|

Special Notes:

Additional options and chemical compatibility in schedule issue no n/a dated n/a.

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

| To test levels of:        | The packaging is approved, as provided in the relevant transport rule, to contain liquids of: |               |             |                 |
|---------------------------|---|---------------|-------------|-----------------|
| DROP HEIGHT (m)           | 2.1   | packing group | density (d) | gross mass (kg) |
| LEAKPROOFNESS (kPa)       | 30  | I             | 1.4         | 37              |
| STACKED AT 3m with RD (d) | 1.4   | II            | 1.4         | 37              |
| INTERNAL PRESSURE (kPa)   | 250   | III           | 1.4         | 37              |

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

Packagings of the sample specifications shall bear the marking:

**UN** 3H1/X1.4/250/\*\*/GB/5987

Revalidation due by: 31/12/ 2026

For further details see [www.vca.gov.uk](http://www.vca.gov.uk)

Signed:

*Keith F.B. White*

Keith F B White. Head of Dangerous Goods VCA DGO

\*\* To be replaced by the last two digits of the year of manufacture

Amendments or additions to this certificate or the design type specification described therein other than those authorised by the certifying body render the certificate invalid.