

# 30L Black Tight-Head Steel Drum with Lacquered Interior

Packaging type: 1A1 Description:  
Drum, steel, non-removable head

Stainless: No Metal thickness Body: 0.80 mm Base: 0.80 mm Head: 0.80 mm Tare: 4.3 kg Capacity: 30 litres  
Tinplated: No Diameter: 286 mm Height: 572 mm Rolling hoop(s): Yes Handle: Strap handle on head

CLOSURES: No in Head: 2 No in Body: 1 Closures may be any of the following:

Steel Size: 2" Type: Screwbung Maker: Tri-Sure Overcap: <input type="checkbox"/> Washer/wad and Closure Torque Rubber 30 Nm Plastics 40 Nm	Steel Size: 3/4" Type: Screwbung Maker: Tri-Sure Overcap: <input type="checkbox"/> Washer/wad and Closure Torque Rubber 10 Nm Plastics 15 Nm	Plastics Size: 2" Type: Steel screwbung Maker: Tri-Sure Overcap: <input type="checkbox"/> Washer/wad and Closure Torque Rubber 30 Nm Plastics 40 Nm	Plastics Size: 3/4" Type: Screwbung Maker: Tri-Sure Overcap: <input type="checkbox"/> Washer/wad and Closure Torque Rubber 10 Nm Plastics 15 Nm	Steel Size: 3/4" Type: Screwbung Maker: Tri-Sure Overcap: <input type="checkbox"/> Washer/wad and Closure Torque Rubber 10 Nm Plastics 15 Nm
---	---	--	--	---

**Special Notes:**

Drum can be provided with or without body beads.

There may be additional options please see full report(s)

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:


To test levels of:

The packaging is approved, as provided in the relevant transport rule, to contain liquids of:

DROP HEIGHT (m)	1.2	packing group	density (d)	gross mass (kg)
LEAKPROOFNESS (kPa)	20	I	-	-
STACKED AT 3m with RD (d)	1.2	II	1.2	41
INTERNAL PRESSURE (kPa)	510	III	1.8	59

**THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT**

Packagings of the sample specifications shall bear the marking:

 1A1/Y/510/\*\*/GB/1447

\*\* To be replaced by the last two digits of the year of manufacture

Revalidation due by: 31/12/ 2018

For further details see [www.vca.gov.uk](http://www.vca.gov.uk)

Signed:

*Keith F.B. White*

Keith F B White, Principal Consultant VCA DGO

Amendments or additions to this certificate or the design type specification described therein other than those authorised by the certifying body render the certificate invalid