

3L White UN Bucket For Solids

PACKAGING DESCRIPTION – RANGE SECURE

Commercial reference	ROPAC® MP 3 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	220,5 mm
Height incl. lid	143 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	0,53 cm ³ /day for 21% oxygen
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 81 kg/24 h/23°C
Option	---



PAIL CHARACTERISTICS – REFERENCE 7503006

Volume brim full	3,7 l (0.97 US gallon)
Volume under lid	3,4 l (0.89 US gallon)
UN certified for a maximum weight of content	4 kg
Weight with handle	196,3 g
Internal diameter at top	201,5 mm
Embossing	Ⓜ 1H2/Y4/S/--/F/BVT/26084
Decoration type	---
Decoration area	---
Standard palletisation (800x1200 NIMP15)	736 pieces (16 piles of 46 pails)
Height of pallet	1,81 m



LID CHARACTERISTICS – REFERENCE 7536030

Weight without gasket	91 g
Diameter	202 mm
Embossing	Ⓜ MP 3-6H
Gasket	SEBS
Standard palletisation (800x1200 NIMP15)	1620 pieces (6 boxes of 270 pcs)
Height of pallet	2,02 m



*These specifications are without legal warranty and subject to changes without notification.
December 2018/ SV*

