

CurTec 55L UN Wide Neck Drum



Product part	Product code	Materials
Drum	6942	HDPE
Handle	6800	HDPE
Lid	6970	HDPE
Gasket	H14	EPDM

Capacity	Liters	US Gallons
Brimful	56	14.79
When closed	55	14.53

Hazardous material information	
Hazardous material type	Solids
Packaging group	I – II – III
UN marking	UN/1H2/X69/S/--/NL/CURTEC 934
Maximum gross mass (kg)	X=69

Weight	Grams	Ounces
Drum	2100	74.07
Handles	90	3.18
Lid	653	23.03
Gasket	37	1.31
Total	2880	101.59

Weight tolerance

All products have a tolerance of $\pm 4\%$ of the initial weight mentioned on this data sheet

Dimensional tolerances

	%
Height	± 2.5
Diameter	± 1.5

Wall thickness

	mm
Minimal wall thickness	≥ 1.9
Nominal wall thickness	≥ 2.3

Colors

	Color code	PMS references
Drum	Black 101	/
Lid	Black 101	/
Handle	Black 101	/

Product identification

	Drum	Lid
Manufacturer ID	Bottom	--
Product code	Bottom	Inside
Recycle logo / Material type	Bottom	Inside
Date clock	Bottom	Outside
UN-mark	Side wall	--
Food logo	Bottom	--
Material track clock	Bottom	--
CFR49-mark	Bottom	--
Mold cavity number	Bottom	Inside

Other information

Maximum filling temperature is 70°C/ 158°F
 Contents must have cooled to 30°C/ 86°F before containers can be closed and stacked
 DoC available on request
 UN certificate available on request
 MVTR declaration available on request
 Watertightness declaration available on request
 User manual available on request
 Preparation for future valve integrated in drum
 All drums can be made tamper evident with application of compact seal # 7800

