

60L UN Open Top Drum

Certificate serial number: 5172

NOT TRANSFERABLE

Application No.: 9765

Issue number and date: 06 02/06/2021

Issued to: GEM PLASTICS LTD
Regaskin
Cavan
Co.Cavan
Ireland

Packaging type: 1H2

Description:

Drum, plastics, removable head

Capacity: 60 litres Bodymass: 2.5 kg Tare mass: 3.6 kg Diameter: 400 mm Rolling hoop(s): No Height: 620 mm

Full aperture: Yes Closing ring: External lever action

Head gasket: Rubber

Handle: 2 x drop handles, one on either side

Test Contents: Tested with fine kiln dried sand and iron weights for solids

No closures in head: 1

Plastics	
Size:	2"
Type:	
6N Screwbung with inset vent plug	
Maker:	
Tri-Sure	
Overcap: <input type="checkbox"/>	
Washer/wad and Closure Torque	
EPDM	13 Nm
	Nm

Special Notes:

Drums can be manufactured from either BASF Lupolen 6021D, Liten VB 33 or Litten VB 58-030. Standard lid is plain, vented lid option via 2" Tri-sure above.

For additional options see schedule issue no n/a date n/a.

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:

The packaging is approved, as provided in the relevant transport rule, to contain solids of:

DROP HEIGHT (m)	1.8	packing group	density (d)	gross mass (kg)
STACKED AT 3m with BD (d)	1.8	I	1.8	112
		II	1.8	112
		III	1.8	112